


REVISIONS			
REV		DATE	APPROVED



SKU # 98001038

Electrical Specifications

- *Frequency Range [MHz] : 360 - 520
- *Insertion Loss [dB] : 0.7 (Typ.)
- *Frequency Sensitivity [dB] : +/- 0.7
- *Coupling [dB] : 7.00 +/- 0.5
- *Isolation [dB] : 20 (Typ.)
- *Pass Band VSWR : 1.25:1 (Typ.)
- *Input/Output Impedance : 50 ohm
- *RF Power Capability CW : 50 Watts

OPERATING TEMPERATURE RANGE: -35°C TO +85°C

PROPRIETARY DOCUMENT:
 THE CONTENTS OF THIS DOCUMENT WITH ALL INFORMATION AND PROCESSES ARE THE SOLE PROPERTY OF G-Way Microwave. THIS DOCUMENT MAY NOT BE DUPLICATED OR DISCLOSED TO ANY PARTY EXCEPT BY EXPRESSLY WRITTEN PERMISSION. THE ONLY AUTHORIZED USE OF THIS DOCUMENT BY A VENDOR IS FOR QUOTE PURPOSES AND SAID VENDOR AGREES NOT TO DISCLOSE ITS CONTENTS TO ANY THIRD PARTY. THIS DOCUMENT IS COPYRIGHTED 1998.

NOTES:

1. BREAK ALL CORNERS & EDGES.005/.010.
2. FINAL FINISH:
 TEXTURED EPOXY BLACK - OPTIONAL.

DIMENSIONS ARE IN INCHES: TOLERANCES ARE ANGLES DECIMALS ± 1" X ± .05 XX ± .01 XXX ± .003		CONTRACT NO:		G-Way Microwave	
TREATMENT		APPROVALS	DATE		
FINISH 63/		DRAWN Sivak 04/07		7 dB Coupler	
MATERIAL AL6061-T6		CHECKED	ENG. DESIGN ACTIVITY	SIZE A	CAGE CODE 3KI14
				DWG NO: MSI-B1600-7	REV. 0
				SCALE None	SHEET 1 OF 1