REVISIONS			
REV		DATE	APPROVED
A	Linearity and power upgraded (PS8-25/33)	11/12	G. David



AVAILABLE OPTIONS	Description



Electrical Specifications

*Down-Link (Base to Mobile) Frequency Range [MHz]		:	758 - 775
		:	851 - 854
*Up-Link (Mobile to Base) Frequency Range [MHz]		:	788 - 809
*Gain (Minimum attenuation) [dB]		:	80 (Min.), 85 (Typ.)
*Gain Flatness [dB]		:	+/- 1.5 (Typ.)
*Noise Figure (System) [dB]		:	5.5 (Max.), 5.0 (Typ.)
*Manual Attenuation Range [dB]		:	0 - 30 in 2-dB steps
*Output Power ALC Set [dBm]	Uplink	:	+25±1
	Downlink	:	+25±1
*Output Composite Power [dBm]	Uplink	:	+25 (Typ.)
	Downlink	:	+25 (Typ.)
*3rd Order Output Intercept Point [dBm] @ 2 tones + 22 dBm each	Uplink	:	+45 (Typ.)
*3rd Order Output Intercept Point [dBm] @ 2 tones + 22 dBm each	Downlink	:	+45 (Typ.)
*Power Supply		:	110V/0.37A to 220V/.19A (Autoranging) 50 to 60 Hz
*Propagation Delay [uSec]		:	<0.3
*Input/Output Impedance		:	50 ohm
*VSWR IN/OUT		:	<1.5:1
*Net Weight		:	< 16 kg/35 lb

*PAINT: FLAT EPOXY BROWN

OPERATING TEMPERATURE RANGE: −30°C TO +55°C

WITHOUT INCLUSION OF ACSP OPTION, THIS UNIT MAY NOT BE POWERED BY A GENERATOR.

WARNING. This is NOT a CONSUMER device. It is designed for installation by FCC LICENSEES and QUALIFIED INSTALLERS. You MUST have an FCC LICENSE or express consent of an FCC Licensee to operate this device. Unauthorized use may result in significant forfeiture penalties, including penalties in excess of $100,000 for each continuing violation.

NEMA 4 ENCLOSURE

SKU # 11602162

FCC ID: Q8KPS7W83790

DIMENSIONS ARE IN INCHES. TOLERANCES ARE: ANGLES ± 1° DECIMALS .X ± .05 .XX ± .01 .XXX ± .003	CONTRACT NO:		**G-Wave Solutions**
	APPROVALS	DATE	TITLE Dual Band BDA 700/800 MHz
	DRAWN Sivak	11/15	BDA-PS7W/NPSPAC/N-25/25-80-C
TREATMENT	CHECKED		SIZE A | CAGE CODE | DWG NO: BDA-PS7W/NPSPAC/N-25/25-80-C-1 | REV. A
FINISH 63	ENG.		
	DESIGN ACTIVITY		
MATERIAL			SCALE None | SHEET 1 OF 1